

# Low Power

External power adapters

3-100 Watts

## Special Features

**All models feature:**

- Wide-range AC input
- High demonstrated MTBF
- Overload protection
- Extensive safety approvals

**Many models feature:**

- EN61000-3-2 compliance
- Medical approvals
- Thermal protection
- Energy Star/ErP
- DoE Level VI
- EU CoC v5 Tier 2

**AC Input:**

- Wallmount
  - U.S. – 2-prong
  - China – 2-prong
  - Europe – 2-prong
  - United Kingdom – 3-prong
  - Australia – 2-prong
  - Korea – 2-prong
  - Japan – 2-prong
  - Interchangeable
- Freestanding
  - IEC320 2-pin (C14) & (C6)
  - IEC320 2-pin (C8)

**DC Output:**

- Single output
  - 2.5 mm barrel plug
  - 2.1 mm right angle plug



Output Power

**3 W**



V1	V2	V3	Size W x L x H (mm)	Model
<b>DCH3 Series – USB (Level VI)</b>				
5 V @ 0.55 A			1.03" x 2.28" x 2.56" (26.1 x 58 x 65)	DCH3-050EU-0005 DCH3-050EU-0006
5 V @ 0.55 A			2.02" x 2.28" x 1.79" (51.2 x 58 x 46)	DCH3-050UK-0005 DCH3-050UK-0006
5 V @ 0.55 A			1.03" x 2.29" x 2.44" (26.1 x 58 x 62)	DCH3-050US-0005 DCH3-050US-0006

**5 W**



V1	V2	V3	Size W x L x H (mm)	Model
<b>DA5 Series (Level VI)</b>				
5 V @ 1 A			1.73" x 1.57" x 0.98" (44 x 40 x 25)	DA5-050US-B DA5-050US-W
5 V @ 1 A			2.48" x 1.57" x 0.98" (63 x 40 x 25)	DA5-050EU-B
5 V @ 1 A			1.93" x 1.65" x 2.17" (49 x 42 x 55)	DA5-050UK-B
5 V @ 1 A			1.73" x 1.57" x 0.98" (44 x 40 x 25)	DA5-050CH-B

**10 W**



V1	V2	V3	Size W x L x H (mm)	Model
<b>DA10 Series (Level VI)</b>				
5 V @ 2 A			1.73" x 1.57" x 0.98" (44 x 40 x 25)	DA10-050US
5 V @ 2 A			1.73" x 1.57" x 0.98" (44 x 40 x 25)	DA10-050CH
5 V @ 2 A			2.48" x 1.57" x 0.98" (63 x 40 x 25)	DA10-050EU
5 V @ 2 A			1.93" x 1.65" x 2.17" (49 x 42 x 55)	DA10-050UK

Output Power	V1	V2	V3	Size W x L x H (mm)	Model
<b>10 W</b> 	<b>DA10-M Series (Level VI)</b>				
	5 V @ 2 A			1.10" x 2.36" x 2.14" (28 x 60 x 54.3)	DA10-050AU-M
	5 V @ 2 A			1.10" x 2.36" x 2.48" (28 x 60 x 63.1)	DA10-050EU-M
	5 V @ 2 A			1.98" x 2.36" x 1.90" (50.2 x 60 x 48.3)	DA10-050UK-M
	5 V @ 2 A			1.10" x 2.36" x 1.99" (28 x 60 x 50.6)	DA10-050US-M
	5 V @ 2 A			1.1" x 2.36" x 2.06" (28 x 60 x 52.3)	DA10-050MP-M <sup>(1)</sup>
	5 V @ 2 A			1.1" x 2.36" x 2.06" (28 x 60 x 52.3)	DA10-050MP-M2.1 <sup>(2)</sup>
5 V @ 2 A			1.1" x 2.36" x 2.06" (28 x 60 x 52.3)	DA10-050MP-M402 <sup>(3)</sup>	
<b>24 W</b> 	<b>AD24 (Level VI)</b>				
12 V @ 2 A			1.89" x 4.13" x 1.3" (48 x 105 x 33)	AD2412N3L-VI	
<b>40 W</b> 	<b>DP40 Series (Level V only)</b>				
	9 V @ 4.4 A			2.4" x 4.88" x 1.55" (61 x 124 x 39.5)	DP4009N2M
	9 V @ 4.4 A				DP4009N3M
	12 V @ 3.33 A				DP4012N2M
	12 V @ 3.33 A				DP4012N3M
	15 V @ 2.67 A				DP4015N2M
	15 V @ 2.67 A				DP4015N3M
	18 V @ 2.22 A				DP4018N2M
	18 V @ 2.22 A				DP4018N3M
	24 V @ 1.67 A				DP4024N2M
	24 V @ 1.67 A				DP4024N3M
48 V @ 0.84 A				DP4048N2M	
48 V @ 0.84 A				DP4048N3M	
<b>45 W</b> 	<b>DA45C Series (45 Watts USB PD 3.0 Type C, Level VI)</b>				
	5 V @ 3 A / 9 V @ 3 A / 15 V @ 3 A / 20 V @ 2.25 A	(Single Output, Changeable)		2.28" x 1.58" x 1.06" (58 x 40.2 x 27)	DA45C-J3WUS
	5 V @ 3 A / 9 V @ 3 A / 15 V @ 3 A / 20 V @ 2.25 A	(Single Output, Changeable)			DA45C-J3WCH
5 V @ 3 A / 9 V @ 3 A / 15 V @ 3 A / 20 V @ 2.25 A	(Single Output, Changeable)			DA45C-J3WEU	
<b>100 W</b> 	<b>DP100 Series (Level VI &amp; PoE Isolation)</b>				
54 V @ 1.85 A			6.14" x 2.56" x 1.46" (156 x 65 x 37.2)	DP10054P3L	

**Options:**

- (1) Interchangeable AC plug - must be purchased separately
- (2) 2.1 mm x 5.5 mm barrel plug
- (3) µUSB connector

**NOTE:**

Level V products may only be imported into the U.S.A. after February 10, 2016 with valid exemptions to Federal Regulations.